

Height Adjusting Blocks for Miniature Linear Guides

Standard Rail Type

Note that, for some of the types shown here, order might be unable to be received by the MISUMI Malaysia, Indonesia, and/or India offices.

Linear Guide Stopper Bolts / Linear Guide Block Stopper Plates

Rail Mounting Hole Caps / Rail Push Plates

Blocks for Miniature Linear Guides. Width/Height tolerance and parallelism are guaranteed.

Type		Material	Surface Treatment
Datum Side	Free Side		
GETA	GETE	S45C Equivalent	Electroless Nickel Plating
AGETA	AGETE	Aluminum Alloy	Clear Anodize

RoHS

Detail of ϕ

Datum Side

Free Side

Part Number	Type	(Slide Guide H Dimension) No.	L Selection								1mm Increment	C	K	Q	N	P	N ₁	P ₁	Tapped Hole M	S Through + Counterbored Hole		
			40	55	70	85	100	115	130	145										160	175	195
GETA		8	40	55	70	85	100	115	130	10-60	7	2	1	5	15	12.5	15	M2	3.5	6	3.5	
AGETA		10	55	75	95	115	135	155	175	195	9	3	1.5	7.5	20	17.5	20	M3	4.5	8	4.5	
GETE		13	70	95	120	145	170	195	220	245	12	3	2	10	25	22.5	25	M3	4.5	8	4.5	
AGETE		16	110	150	190	230	270	310	350	390	15	3	3	15	40	35	40	M3	5.5	9.5	5.5	
		20	160	220	280	340	400	460			20	3	4	20	60	50	60	M5	6.5	11	6.5	

When T ≤ Mx4, the pilot holes for tapping go through.

Ordering Example: Part Number - L - T

Example: GETA10 - 115 - 20

Price List

No.	L	Unit Price			
		GETA	AGETA	GETE	AGETE
8	40				
8	55				
8	70				
8	85				
8	100				
8	115				
8	130				
10	55				
10	75				
10	95				
10	115				
10	135				
10	155				
10	175				
10	195				
10	215				
10	235				
10	255				
10	275				
13	70				
13	95				
13	120				
13	145				
13	170				
13	195				
13	220				
13	245				
13	270				
13	295				
13	320				
13	345				
13	370				
13	395				
16	110				
16	150				
16	190				
16	230				
16	270				
16	310				
16	350				
16	390				
16	430				
16	470				
20	160				
20	220				
20	280				
20	340				
20	400				
20	460				

Applicable Linear Guides

P533-P554 Compatible with Miniature Linear Guides L Selectable Types.

- H13 is not applicable to L420 or more.
- H16 is not applicable to L510 or more.
- H20 is not applicable to L520 or more.

Linear Guide Stopper Bolts

Type	Material	Surface Treatment
SBLT	SUS303	
SBLTJ	Knurled Head (Urethane Shore A80)	Electroless Nickel Plating
SBLTJ	Threaded Section	SUS304

* SBLTJ is a hex socket set screw with a heat bonded urethane head.

RoHS

Part Number	Type	M (Coarse)	L	A	D	B				t	Unit Price	Volume Discount Rate					
						SBLT	SBLTJ	SBLT	SBLTJ								
SBLT		3	8	10	12	6	8	10	5.5	2.5	1.5	3	2	1 - 9 pc(s)	10 - 30 pcs	1 - 9 pc(s)	10 - 30 pcs
SBLTJ		4	10	8	7	3	2	3.5	2.5								
		5	16	18	14	8.5	4	2.5	4	3							
		6	18	20	10	5	3	5	3.5								

For orders larger than indicated quantity, please request a quotation.

Linear Guide Block Stopper Plates

SVP24 SVP28 SVP33

RoHS

Rail ends require tapping alterations. TMS alterations are available with economical charge. See P570, 576, 598, 604 and 606. Applicable to existing products of Linear Guides for Medium/Heavy Load, Carbon Steel Type only. Material: SUS304D

Part Number	Type	No.	A	B	C	ℓ	Unit Price	Volume Discount Rate
		28	26	15	19	6		
		33	29	19	22	7		

For orders larger than indicated quantity, please request a quotation.

Rail Mounting Hole Caps (Package)

PACK-SGLC

RoHS

Material: Polyacetal (Black)

Part Number	Type	M (Applicable Screw Hole)	D	P	T (d)	Qty. per Pkg.	Unit Price
PACK-SGLC		3	5.8	6.2	1.5	4.2	100 pcs./pkg.
		5	9.3	9.7	3	7.3	100 pcs./pkg.
		6	10.8	11.2	3	8.8	100 pcs./pkg.

PACK-SGLC3 has 4 protrusions. Prevents foreign substances such as cutting chips from intruding into mounting holes. For orders larger than indicated quantity, please request a quotation.

Rail Push Plates

SGU

RoHS

Type	Part	Material	Surface Treatment
SGU	① Main Body	S45C	Electroless Nickel Plating
	② Screw	SUS304	

Part Number	Type	H	L Selection	Tapped Hole M	Included Screw Size	Unit Price	Volume Discount Rate		
								SGU	5
		6	40	100	340	4	M4-12		

For orders larger than indicated quantity, please request a quotation.

